

MY24 OUTLANDER 6X6 XU+ 450 T



Tundra Green

HIGHLIGHTS

- Selectable 4WD / 6WD front differential
- Tri-Mode Dynamic Power Steering (DPS)
- Continuously Variable Transmission (CVT) with extra low L-gear
- 12 in. (30.5 cm) cast-aluminum wheels
- 26 in. (66 cm) Carlisle† ACT HD 6-Ply tires
- 3,500-lb (1,588 kg) winch
- Heavy-duty front bumper
- Heated grips and throttle
- Rear bed with cargo extenders
- Speed limiter

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	443 kg
L x W x H	279 x 118.8 x 147.4 cm
Wheelbase	208 cm
Ground Clearance	26.7 cm
Seat Height	85.8 cm
Rack Capacity	Front: 54 kg / Rear: 159 kg
Storage Capacity	2.9 gal (10.9 L)
Towing Capacity	907 kg trailer with brakes 465 kg trailer without brakes
Fuel Capacity	5.4 gal (20.5 L)

FEATURES

Gauge	4.5 in. digital display
Instrumentation	DC Outlet, 15-A connector
Ignition	Mechanical key
Lighting	70 W headlights
Winch	3,500-lb (1,588 kg) winch
T-Category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn
Seat	Reinforced seat skin
Handlebar	Standard with heated grips & throttle
Protection	Heavy-Duty front bumper

WARRANTY

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------

ENGINE

Type	28 kW (38 hp), Rotax® 427 cc single cylinder, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT Extra low L / H / N / R / P
Drive Train	Selectable 4WD / 6WD with Visco-Lok† QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed Category	Up to 60 km/h

SUSPENSIONS

Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Twin tube
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 8.8 in. (22.4 cm) travel
Rear Shocks	Twin tube

TIRES / WHEELS

Front Tires	Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. (30.5 cm) cast-aluminum

BRAKES

Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †All trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by the age of 16 and older. Never carry passengers on any ATV not specifically designated for such use. Some models depicted may include optional equipment.



REQUEST A QUOTE

